






Great suction power, also with hirsute people. Very good ECG quality, easy to operate, quiet.
An all-round impressive device!"

Various fastenings provide the *handy* vaq with a broad range of applications. The entire *handy* vaq unit can be sterilised and is also easy to clean with the blow-out function.

handy vaq

Easy to use. Small. Powerful.

The *handy vaq* is probably the smallest ECG suction device on the market. The quiet, high-performance and maintenance-free pump is integrated directly into the compact control housing. The light device can be held securely in one hand owing to the side anti-slip inserts.



Reduced to just a few components, handy vaq is particularly easy to service. If necessary, the sturdy plugin components can be exchanged quickly and inexpensively. handy vaq is the user-friendly, flexible all-in-one solution that will facilitate your work and you will be impressed by its excellent price-performance ratio.

The powerful features of the handy vaq are impressive



Compact all-in-one solution

handy vaq is only palm-sized. The powerful, but quiet pump is integrated in the compact, anti-slip housing.



Very simple to operate

The device is operated by using only three keys. LED displays the status. The vacuum power can be adjusted in five settings ranging from 100 to 250 mbar.



Excellent signal quality

handy vaq has very good signal quality for 10 leads.



Simply hygienic

There is a blow-out function on the *handy vaq* to blow out moisture and impurities.



Universal use

handy vaq can be used flexibly.



Electrode cables

The cable assemblies have silver/silver chloride electrodes with soft silicon suction domes.



Easy to service

A few maintenance-free components with plug connections permit easy and therefore low-cost servicing. The patient cables can be replaced individually.



Comprehensive user guide

A comprehensive user guide with operating instructions, safety information and practical tips is supplied with the *handy vaq* suction unit.

handy Vaq ECG vacuum

Technical data





handy vaq module

Dimensions	$78 \times 117 \times 27$ mm (without cables)
Weight	950 g, with set of cables
Power supply	Mean Well GEM12i05-USB
Environmental conditions Ambient temperature Relative humidity	10 – 50 °C 30 – 75 % (not condensing)
Air pressure	700 – 1,060 mbar
Partial vacuum - max. vacuum	250 mbar
5 partial vacuum settings	100 / 130 / 170 / 210 / 250 mbar
Volume	2.7 l/min
ECG connection	15-pol. D-Sub, 2 m long

Patient cables

Chest 6 pieces	1.1 m (length of cable assembly)
Extremities 4 pieces	1.3 m (length of cable assembly)
Electrodes	Ag/AgCl, cup material silicone

Safety standards

Safety standard	IEC/EN 60601-1
EMC	IEC/EN 60601-1-2, 4. Edition
Classification	Class I in accordance with Directive 93/42/EEC
Protection	This device is not designed for outdoor use (IPXO)

Scope of delivery

Scope of delivery	
Standard	Suction/control unit, 2 m connection cable (USB/15-pol D-Sub), 10 lead patient cable (standard length 1.1-1.3 m), USB network adapter, cable spacer, removal tool





Pat. pending



mbnet Engineering GmbH

Kirschauer Str. 37a
OT Callenberg
02681 Schirgiswalde-Kirschau
Germany
Phone +49 35 92 34 83 0 and 54 25 47
Fax +49 35 92 34 34 4 and 54 25 49
verkauf@mbnet.de
www.mbnet.de